

ABOUT SRNE

- \square SRNE 15 years in PV industry, committed to independent R&D and production.
- ☐ Holds over 200 patents in energy storage, with unique industryleading technologies.
- ☐ Chooses top-quality international components to deliver highvalue products to customers.
- ☐ Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.



MODEL		HF2430S60-100		
INVERTER OUTPUT				
Rated Output Power		3,000W		
Max.Peak Power		6,000VA		
Rated Output Voltage		230Vac (Single-Phase)		
Load Motor Capacity		2HP		
Rated Frequency		50/60Hz		
Waveform		Pure sine wave		
Switch Time		10ms (typical)		
BATTERY				
Battery Type		Lead-Acid / Li-ion / User-Define		
Rated Battery Voltage		24V		
Battery Volatge Range		20~33Vdc		
Max. Solar Charging Current		60A		
Max. Grid/Generator Charging Current		A08		
Max. Hybrid Charging Current		140A		
SOLAR INPUT				
No. Of MPPT		1		
Max.PV Array Power		1,600W		
Max. Input Current		40A		
Max. Open Circuit Voltage		108Vdc		
MPPT Voltage Range		30~90Vdc		
GRID/GENERATOR INPUT				
Input Voltage Range		170~280Vac		
Input Frequency Range		50/60Hz		
Bypass Overload Current		30A		
EFFICIENCY				
MPPT Tracking Efficiency		99.9%		
Max. Efficiency		92%		
GENERAL DATA				
Dimension	37	8*280*103mm	Moisture	5%~95%
Weight		6.8kg	Cooling Method	Fan Cooling
Protection Degree	IP20 Only Indoor		Warranty	2 years
Temperature		-10°C~55°C	Communication	RS485/CAN/USB/Dry Contac
External Module (Optional)		Wi-Fi/GPRS	Topology	Transformerless
Certificate	Roh	RoHs/EN61000/IEC 62109/PSE Circular Certification		

PROTECTION

Equipped with PV current limit and power limit protection, PV night anti-reverse charging protection, utility input over-voltage protection, utility input under-voltage protection, battery over-voltage protection, battery under-voltage protection, load output short-circuit protection, radiator over-temperature protection, over-load protection, PV anti-reverse protection, AC back-filling protection, bypass overcurrent protection, battery input overcurrent protection, battery input protection, charging short-circuit protection,.